

Terminus Processors are UL-Listed and feature microprocessor-based SMD (surface mount device) technology, individual relay outputs, as well as a choice of glass-break or count select mode. Terminus processors monitor Terminus shock sensors on a wide variety of surfaces including all types of glass, fencing, masonry, or wallboard.

SP3268 Terminus One Zone Processor can be used to monitor up to fifty sensors on a single zone. The unit comes in a hinged metal enclosure equipped with a key lock and tamper switch. The enclosure measures 13½" x 9½" x 3¼" and has a slide switch on the front panel. The unit is shipped with a standby battery and transformer. The One Zone Processor is particularly effective on smaller chain link fence applications.

SP3274 Terminus Four Zone Processor allows a protected area to be divided into four zones, monitoring up to 50 sensors per zone. Each zone can be adjusted individually for optimum performance. The panel monitors up to four loops of Terminus sensors, protecting walls, windows, and/or fences - each with its own set-up adjustments. The unit comes in a hinged, metal enclosure that measures 13½" x 9½" x 3¼" and is designed to be installed in a secure indoor location.

The Four Zone Processor has an AC power LED, a four position test-function key switch and a master relay. Each of the four zones has its own LED indicators, on/off switch, SPDT relay, and mode select switch for multiple-event-count of glass-break detection. The Four Zone Processor features a programmable entry/exit time delay on each zone. It is designed to monitor the first four zones with one Terminus Four Zone Expander Processor required for each additional four zones. The Four Zone Processor is shipped with a standby battery and transformer.

SP3273 Terminus Four Zone Expander Processor monitors up to four additional zones of Terminus sensors with the same capability as the Four Zone Processor and it is housed in the same hinged, metal enclosure. The expander is shipped with a standby battery and the plug-in terminals and cable necessary to connect to the Four Zone Processor.

Terminus Works. Other Terminus perimeter intrusion detection products include Terminus shock sensors for windows, walls and fence applications.

For more information about our Terminus Processors and the complete line of Terminus perimeter intrusion detection systems contact us at 1.866.680.TERM (8376).

